Quantum EVM Ltd.
飞腾磁动力有限公司

www.qtevm.com

QTEVM.com			225 Compact	225 SUV	225 Performance	260Sport	260 Mini Bus
			400V DC	400V DC	600V DC	600V DC	600V DC
Max. Rating		单位					
Max. Torque		NM	227 / PF 0.8	320 / PF 0.82	424 NM / PF 0.82	700 NM / PF 0.79	655 NM / PF 0.75
Max. Current	3 Phase Motor Terminal	A	240	480	340	530	318
	DC from Battery	A	340	340	480	750	450
Max. Speed		RPM	6500	6500	6500	7500	4200
Max.Power		KW	115	160	215	362	212
			@6000 RPM / 183NM	@6000 RPM / 260 NM	@6000 RPM / 342 NM	@6000 RPM / 577 NM	@3800 RPM / 655 NM
Continuous Rating		单位					
Continuous Torque		NM	118	165	220	370	317
Continuous Current	3 Phase Motor Terminal	A	120	170	170	260	145
	DC from Battery	A	170	240	340	375	205
Continuous Speed		RPM	4500	4500	4500	4500	2800
Continuous Power		KW	56	80	108	175	93
Mechanical							
Wire Temperature Rating		Degree C	180	180	180	180	180
VPI Temperature		Degree C	200	200	200	200	200
Liquid Cool			Yes	Yes	Yes	Yes	Yes
Motor Diameter		CM	25	25	25	30	30
Motor Length		CM	20	24	28	32	28
Weight		KG	40	55	70	125	125

sales@qtevm.com